

**Table 2. Pertinent Data for Fish Facility Inspections in 2014 at THE DALLES DAM.**

| <b>CRITERIA ITEMS</b>   |    |                           |                      |                      |                      |                      |                      |                     |                      |
|---|----|---------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|---------------------|----------------------|
|   |    | <b>DATE OF INSPECTION</b> |                      |                      |                      |                      |                      |                     |                      |
| <b>SOUTH SHORE FISHWAY</b>  |    | <b><u>25-Mar</u></b>      | <b><u>21-Apr</u></b> | <b><u>29-May</u></b> | <b><u>26-Jun</u></b> | <b><u>29-Jul</u></b> | <b><u>26-Aug</u></b> | <b><u>1-Oct</u></b> | <b><u>28-Oct</u></b> |
| <b>East Entrance:</b>   |    |                           |                      |                      |                      |                      |                      |                     |                      |
| <b>Depth over entrance weir</b>   |    |                           |                      |                      |                      |                      |                      |                     |                      |
| E-1 (gate set at elev. 83.5 ft)   | ft | NA                        | NA                   | NA                   | NA                   | NA                   | NA                   | NA                  | NA                   |
| E-2 (crit. = 8 ft or >)   | ft | 12.1                      | 12.0                 | 12.6                 | 12.5                 | 14.0                 | 10.9                 | 13.1                | 11.9                 |
| E-3 (crit. = 8 ft or >)   | ft | 12.0                      | 11.1                 | 12.4                 | 11.9                 | 9.8                  | 11.6                 | 12.4                | 13.2                 |
| Head at main entrance (crit. = 1-2 ft)  | ft | 1.3                       | 1.5                  | 1.4                  | 1.4                  | 1.5                  | 1.5                  | 1.7                 | 1.5                  |
| Depth over ladr. weir (crit. = 1-1.3 ft)  | ft | 1.0                       | 1.0                  | 1.0                  | 1.0                  | 1.3                  | 1.0                  | 1.0                 | 1.0                  |
| Ladder exit clean (yes or no)   |    | yes                       | yes                  | yes                  | yes                  | yes                  | yes                  | yes                 | yes                  |
| Selsyns/PLC operating (yes or no)   |    | yes                       | yes                  | yes                  | yes                  | yes                  | yes                  | yes                 | yes                  |
| Picket leads clean (yes or no)  |    | yes                       | yes                  | yes                  | yes                  | yes                  | yes                  | yes                 | yes                  |
| <b>West Entrance:</b>   |    |                           |                      |                      |                      |                      |                      |                     |                      |
| <b>Depth over entrance weir</b>   |    |                           |                      |                      |                      |                      |                      |                     |                      |
| W-1 (crit. = 8 ft or >)   | ft | 9.5                       | 9.0                  | 11.9                 | 9.5                  | 8.2                  | 8.9                  | 10.0                | 10.0                 |
| W-2 (crit. = 8 ft or >)   | ft | 9.6                       | 9.1                  | 11.9                 | 9.6                  | 8.2                  | 9.1                  | 9.6                 | 10.0                 |
| W-3 (crit. = 8 ft or >)   | ft | NA                        | NA                   | NA                   | NA                   | NA                   | NA                   | NA                  | NA                   |
| Head at main entrance (crit. = 1-2 ft)  | ft | 1.4                       | 1.5                  | 1.5                  | 1.6                  | 1.5                  | 1.5                  | 1.6                 | 1.7                  |
| <b>South Entrance:</b>  |    |                           |                      |                      |                      |                      |                      |                     |                      |
| <b>Depth over entrance weir</b>   |    |                           |                      |                      |                      |                      |                      |                     |                      |
| S-1 (Crit. = 8 ft or >)   | ft | 10.0                      | 9.0                  | 10.5                 | 9.5                  | 8.9                  | 9.1                  | 9.1                 | 9.1                  |
| S-2 (Crit. = 8 ft or >)   | ft | 10.1                      | 10.2                 | 10.6                 | 9.5                  | 9.0                  | 9.1                  | 9.1                 | 9.0                  |
| Head at main entrance (Crit. = 1-2 ft)  | ft | 1.6                       | 1.5                  | 1.5                  | 1.6                  | 1.5                  | 1.5                  | 1.4                 | 1.6                  |
| <b>NORTH SHORE FISHWAY</b>  |    |                           |                      |                      |                      |                      |                      |                     |                      |
| <b>North Shore Entrance:</b>  |    |                           |                      |                      |                      |                      |                      |                     |                      |
| <b>Depth over entrance weir</b>   |    |                           |                      |                      |                      |                      |                      |                     |                      |
| N-1 (crit. = 8 ft or >)   | ft | 9.2                       | 9.6                  | 9.3                  | 9.8                  | 10.1                 | 9.8                  | 9.3                 | 9.1                  |
| Head at main entrance (Crit. = 1-2 ft)  | ft | 1.4                       | 1.3                  | 1.4                  | 1.4                  | 1.2                  | 1.2                  | 1.4                 | 1.5                  |
| Depth over ladr. weir (Crit. = 1-1.3 ft)  | ft | 1.0                       | 1.1                  | 1.1                  | 1.3                  | 0.9                  | 1.0                  | 1.0                 | 1.5                  |
| Ladder exit clean   |    | yes                       | yes                  | yes                  | yes                  | yes                  | yes                  | yes                 | yes                  |
| Selsyns operating   |    | yes                       | yes                  | yes                  | yes                  | yes                  | yes                  | yes                 | yes                  |
| Picket leads clean  |    | yes                       | yes                  | yes                  | yes                  | yes                  | yes                  | yes                 | yes                  |
| PUD trash rack clean (yes or no)  |    | 0.4                       | 0.3                  | 0.4                  | 0.3                  | 0.4                  | 0.5                  | 0.5                 | 0.5                  |
| <b>Comment Number (if applicable)</b>   |    | 1                         |                      |                      |                      |                      |                      |                     |                      |
| <b>Comments</b>   |    |                           |                      |                      |                      |                      |                      |                     |                      |
| 1. PUD screen differential a little high due to cleaning of trash racks, will clean more frequently when trash racks being cleaned. |    |                           |                      |                      |                      |                      |                      |                     |                      |